

# Efficient structure-preserving model reduction for nonlinear mechanical systems with application to structural dynamics

Kevin Carlberg, Ray Tuminaro, Paul Boggs

Sandia National Laboratories

53rd AIAA Structures, Structural Dynamics, and Materials  
Conference

# Time-critical applications

- real-time applications
  - structural health monitoring
  - embedded control
- many-query applications
  - design optimization
  - uncertainty quantification

inputs  $\mu \rightarrow$  high-fidelity model  $\rightarrow$  outputs  $y$

- **barrier**: simulation can take days on supercomputers
- model reduction

inputs  $\mu \rightarrow$  reduced-order model  $\rightarrow$  outputs  $y$

- *offline* (expensive): 'training' analyses
- *online* (cheap): deploy low-dimensional model

- high-fidelity model
  - *parameterized* simple mechanical system
  - nonlinear potential energy
  - Rayleigh damping
  - external force
- existing reduced-order models
  - 1 preserve structure, but remain expensive
  - 2 destroy structure, but are cheap
- **our proposed reduced-order model**
  - preserves structure and is cheap

- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example

- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example

# Lagrangian description of structural dynamics

- equations of motion from finite-element discretization

$$M(\mu)\ddot{q} + C(\mu)\dot{q} + \nabla_q V(q; \mu) = f^{\text{ext}}(t; \mu).$$

- can be derived via Lagrangian dynamics with five 'ingredients':

- 1 configuration space  $Q = \mathbb{R}^N$
- 2 Riemannian metric  $g(v, w; \mu) = v^T M(\mu)w$
- 3 potential-energy function  $V(q; \mu)$
- 4 dissipation function  $\mathcal{F}(\dot{q}, \mu) = \frac{1}{2}\dot{q}^T C(\mu)\dot{q}$
- 5 external force derived from the Lagrange–D'Alembert principle  $f^{\text{ext}}(t; \mu)$

- properties 1–3 define a *simple mechanical system*
- properties 4–5 characterize *non-conservative forces*

# Equations of motion: derived from five ingredients

- configuration space:  $q \in Q = \mathbb{R}^N$
- kinetic energy:  $T(\dot{q}; \mu) = \frac{1}{2}g(\dot{q}, \dot{q}; \mu) = \frac{1}{2}\dot{q}^T M(\mu)\dot{q}$
- Lagrangian:

$$\begin{aligned} L(q, \dot{q}; \mu) &= T(\dot{q}; \mu) - V(q; \mu) \\ &= \frac{1}{2}\dot{q}^T M(\mu)\dot{q} - V(q; \mu). \end{aligned}$$

- non-conservative forces

$$F(t, q, \dot{q}; \mu) = f^{\text{ext}}(t; \mu) - \nabla_{\dot{q}} \mathcal{F}(\dot{q}; \mu)$$

- apply forced Euler–Lagrange equations

$$\frac{d}{dt} \nabla_{\dot{q}} L(q, \dot{q}; \mu) - \nabla_q L(q, \dot{q}; \mu) = F(t, q, \dot{q}; \mu)$$

$$\boxed{M(\mu)\ddot{q} + C(\mu)\dot{q} + \nabla_q V(q; \mu) = f^{\text{ext}}(t; \mu)}$$

# Key properties

- conservative mechanical systems ( $F = 0$ )
  - energy conservation
  - momentum conservation
  - dynamics satisfy variational principle
  - symplectic time-evolution maps
- structure-preserving time integration  
[Marsden and West, 2001, Hairer et al., 2006]
  - discrete system preserves some of the above properties
  - leads to improved long-time behavior

**reduced-order models should preserve these properties**



- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example

- determine low-dimensional basis  $\Phi \in \mathbb{R}^{N \times m}$ 
  - modal decomposition, proper orthogonal decomposition
- substitute  $q = \Phi q_r$  to obtain ‘reduced ingredients’
  - 1 configuration space  $Q_r = \mathbb{R}^m$  with  $\mathbf{Q}_r \equiv \{\Phi q_r \mid q_r \in Q_r\}$
  - 2 Riemannian metric  $g_r(v_r, w_r; \mu) \equiv g(\Phi v_r, \Phi w_r; \mu)$
  - 3 potential-energy function  $V_r(q_r; \mu) \equiv V(\Phi q_r; \mu)$
  - 4 dissipation function  $\mathcal{F}_r(\dot{q}_r; \mu) \equiv \mathcal{F}(\Phi \dot{q}_r; \mu)$
  - 5 external force  $f_r^{\text{ext}} = \Phi^T f^{\text{ext}}$
- forced Euler–Lagrange equations yield

$$\Phi^T M(\mu) \Phi \ddot{q}_r + \Phi^T C(\mu) \Phi \dot{q}_r + \Phi^T \nabla_q V(\Phi q_r; \mu) = \Phi^T f^{\text{ext}}(t; \mu)$$

- + preserves Lagrangian structure
- remains expensive for parameterized, nonlinear systems

# Computational bottleneck

$$\Phi^T M(\mu) \Phi \ddot{q}_r + \Phi^T C(\mu) \Phi \dot{q}_r + \Phi^T \nabla_q V(\Phi q_r; \mu) = \Phi^T f^{\text{ext}}(t; \mu)$$

- when  $\mu$  changes, must recompute  $\Phi^T M(\mu) \Phi$  and  $\Phi^T C(\mu) \Phi$ 
  - $\mathcal{O}(Nm^2)$  operations: scales with large dimension  $N$

$$\Phi^T M(\mu) \Phi = \Phi^T M(\mu) \Phi$$

- when  $q_r$  changes, must recompute  $\Phi^T \nabla_q V(\Phi q_r; \mu)$ 
  - $\mathcal{O}(Nm)$  operations

- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example

$$\Phi^T M(\mu) \Phi \ddot{q}_r + \Phi^T C(\mu) \Phi \dot{q}_r + \Phi^T \nabla_q V(\Phi q_r; \mu) = \Phi^T f^{\text{ext}}(t; \mu)$$

- compute subset of equations before performing Galerkin projection

$$\begin{aligned} \Phi^T Z^T Z M(\mu) \Phi \ddot{q}_r + \Phi^T Z^T Z C(\mu) \Phi \dot{q}_r + \Phi^T Z^T Z \nabla_q V(\Phi q_r; \mu) \\ = \Phi^T Z^T Z f^{\text{ext}}(t; \mu). \end{aligned}$$

'sampling matrix'  $Z$ :  $n_Z \ll N$  rows of identity matrix

- destroyed properties:
  2. mass matrix not symmetric: does not define a metric
  3. stiffness matrix not symmetric: does not derive from a potential-energy function
  4. dissipation matrix not symmetric: does not derive from a dissipation function

# Empirical interpolation/least-squares approximation

[Grepl et al., 2007, Nguyen and Peraire, 2008, Chaturantabut et al., 2010, Carlberg et al., 2011]

$$\Phi^T M(\mu) \Phi \ddot{q}_r + \Phi^T C(\mu) \Phi \dot{q}_r + \Phi^T \nabla_q V(\Phi q_r; \mu) = \Phi^T f^{\text{ext}}(t; \mu)$$


- interpolate functions before performing Galerkin projection

$$\Phi^T \tilde{f}_1(\ddot{q}_r; \mu) + \Phi^T \tilde{f}_2(\dot{q}_r; \mu) + \Phi^T \tilde{f}_3(q_r; \mu) = \Phi^T \tilde{f}^{\text{ext}}(t; \mu)$$

$\tilde{f} = \Phi_f [Z \Phi_f]^+ Z f$ : least-squares approximation of  $f$

- destroyed properties:
  2. mass matrix not symmetric: does not define a metric
  3. stiffness matrix not symmetric: does not derive from a potential-energy function
  4. dissipation matrix not symmetric: does not derive from a dissipation function

# Existing complexity-reduction methods




- + leads to  $N$ -independent cost
- destroys Lagrangian structure

# Outline

- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example



# Proposed complexity-reduction method



- + leads to  $N$ -independent cost
- + preserves Lagrangian structure

- directly approximate reduced Lagrangian ingredients
  - 1 configuration space  $Q_r = \mathbb{R}^m$  with  $\mathbf{Q}_r \equiv \{\Phi q_r \mid q_r \in Q_r\}$
  - 2 Riemannian metric  $\tilde{g}_r \approx g_r$
  - 3 potential-energy function  $\tilde{V}_r \approx V_r$
  - 4 dissipation function  $\tilde{\mathcal{F}}_r \approx \mathcal{F}_r$
  - 5 external force  $\tilde{f}_r^{\text{ext}} \approx f_r^{\text{ext}}$

# Approximated reduced Lagrangian ingredients

- 1 configuration space  $Q_r = \mathbb{R}^m$  with  $\mathbf{Q}_r \equiv \{\Phi q_r \mid q_r \in Q_r\}$
- 2 Riemannian metric  $\tilde{g}_r \approx g_r$
- 3 potential-energy function  $\tilde{V}_r \approx V_r$
- 4 dissipation function  $\tilde{\mathcal{F}}_r \approx \mathcal{F}_r$
- 5 external force  $\tilde{f}_r^{\text{ext}} \approx f_r^{\text{ext}}$

## External-force approximation $\tilde{f}_r^{\text{ext}}$

- least-squares approximation of external force

$$\tilde{f}^{\text{ext}} = \Phi_f [Z\Phi_f]^+ Zf^{\text{ext}} \approx f^{\text{ext}}$$

- apply Lagrange–D'Alembert principle to  $\tilde{f}^{\text{ext}}$  with variations in reduced configuration space:

$$\tilde{f}_r^{\text{ext}} = \Phi^T \tilde{f}^{\text{ext}} = \Phi^T \Phi_f [Z\Phi_f]^+ Zf^{\text{ext}}$$

- Offline (expensive)

- 1 collect snapshots of the external force and compute basis  $\Phi_f$
- 2 determine sampling matrix  $Z$
- 3 compute small-scale matrix  $A = \Phi^T \Phi_f [Z\Phi_f]^+$

- Online (cheap)

- 1 compute a few entries of the external force  $Zf^{\text{ext}}$
- 2 compute small-scale product  $A[Zf^{\text{ext}}]$

# Approximated reduced Lagrangian ingredients

- 1 configuration space  $Q_r = \mathbb{R}^m$  with  $\mathbf{Q}_r \equiv \{\Phi q_r \mid q_r \in Q_r\}$
- 2 Riemannian metric  $\tilde{g}_r \approx g_r$
- 3 potential-energy function  $\tilde{V}_r \approx V_r$
- 4 dissipation function  $\tilde{\mathcal{F}}_r \approx \mathcal{F}_r$
- 5 external force  $\tilde{f}_r^{\text{ext}} \approx f_r^{\text{ext}}$

# Riemannian-metric and dissipation-function approximations

$$g_r(v_r, w_r; \mu) = v_r^T \left[ \Phi^T M(\mu) \Phi \right] w_r$$

$$\mathcal{F}_r(\dot{q}_r; \mu) = \dot{q}_r^T \left[ \Phi^T C(\mu) \Phi \right] \dot{q}_r$$

- approximated quadratic ingredients:

$$\tilde{g}_r(v_r, w_r; \mu) = v_r^T \tilde{M}_r(\mu) w_r$$

$$\tilde{\mathcal{F}}_r(\dot{q}_r; \mu) = \dot{q}_r^T \tilde{C}_r(\mu) \dot{q}_r$$

- relies on approximating low-dimensional matrices

$$\tilde{M}_r(\mu) \approx \left[ \Phi^T M(\mu) \Phi \right] > 0$$

$$\tilde{C}_r(\mu) \approx \left[ \Phi^T C(\mu) \Phi \right] \geq 0$$

# Mass-matrix approximation (similar for $C$ )

## ■ Offline (expensive)

- 1 collect matrix snapshots  $\{M_i\}$  and corresponding  $\{\Phi^T M_i \Phi\}$
- 2 determine 'sample entries'

## ■ Online (cheap)

- 1 compute only sample entries of  $M(\mu)$
- 2 solve cheap optimization problem for  $\alpha_i$ :

$$\underset{\alpha_1, \alpha_2}{\text{minimize}} \quad \left\| \begin{array}{c} \begin{array}{|c|} \hline \begin{array}{c} \text{matrix } M(\mu) \end{array} \\ \hline \end{array} - \alpha_1 \begin{array}{|c|} \hline \begin{array}{c} \text{matrix } M_1 \end{array} \\ \hline \end{array} - \alpha_2 \begin{array}{|c|} \hline \begin{array}{c} \text{matrix } M_2 \end{array} \\ \hline \end{array} \right\|_F$$

$$\text{subject to} \quad \alpha_1 \Phi^T M_1 \Phi + \alpha_2 \Phi^T M_2 \Phi > 0$$

- 3 set  $\tilde{M}_r(\mu) = \sum_i \alpha_i \Phi^T M_i \Phi$

# Approximated reduced Lagrangian ingredients

- 1 configuration space  $Q_r = \mathbb{R}^m$  with  $\mathbf{Q}_r \equiv \{\Phi q_r \mid q_r \in Q_r\}$
- 2 Riemannian metric  $\tilde{g}_r \approx g_r$
- 3 potential-energy function  $\tilde{V}_r \approx V_r$
- 4 dissipation function  $\tilde{\mathcal{F}}_r \approx \mathcal{F}_r$
- 5 external force  $\tilde{f}_r^{\text{ext}} \approx f_r^{\text{ext}}$



# Potential-energy function approximation

$$V_r(q_r; \mu) \equiv V(\Phi q_r; \mu)$$

- replace  $\Phi$  with a sparse matrix  $\Psi$  ( $n_Z \ll N$  nonzero rows)

$$\tilde{V}_r(q_r; \mu) \equiv V(\Psi q_r; \mu).$$

- cost reduction
  - $\nabla_{q_r} V_r(q_r; \mu) = \Phi^T \nabla_q V(\Phi q_r; \mu)$  incurs  $\mathcal{O}(Nm)$  flops
  - $\nabla_{q_r} \tilde{V}_r(q_r; \mu) = \Psi^T \nabla_q V(\Psi q_r; \mu)$  incurs  $\mathcal{O}(n_Z m)$  flops
- compute  $\Psi$  by matching  $\Psi^T \nabla_q V(\Psi q_r; \mu)$  and  $\Phi^T \nabla_q V(\Phi q_r; \mu)$  for 'training' values of  $q_r$  and  $\mu$

# Potential-energy function approximation

## ■ Offline (expensive)

- 1 collect snapshots of  $\nabla_{q_r} V_r(q_r; \mu)$  for 'training' values of  $q_r, \mu$
- 2 determine nonzero rows of  $\Psi$
- 3 solve optimization problem


$$\underset{\Psi}{\text{minimize}} \sum_{j=1}^J \left\| \Psi^T \nabla_q V(\Psi q_r^j; \mu^j) - \Phi^T \nabla_q V(\Phi q_r^j; \mu^j) \right\|_2^2.$$

## ■ Online (cheap): replace $V_r$ with $\tilde{V}_r$

# Outline

- 1 Motivation
- 2 Problem formulation
- 3 Existing model-reduction techniques
  - preserves structure, but expensive
  - cheap, but destroys structure
- 4 Proposed method
- 5 Numerical example

## Simple example: conservative clamped-free truss




$$M(\mu)\ddot{q} + \nabla_q V(q; \mu) = 0$$

- $V$ : potential energy, *high-order nonlinearity in  $q$*
- density  $\rho = 1 + \mu_1$
- bar cross-sectional area  $A = 1 + \mu_2$
- modulus of elasticity  $E = 1 + \mu_3$
- $\mu_i \in [-1, 1]$ ,  $i = 1, \dots, 6$
- 120 dofs in 'high-fidelity' model
- time integrator: implicit midpoint rule (symplectic)

# Reduced-order models

- 1 Galerkin projection
    - + preserves structure
    - expensive
  - 2 Galerkin projection + collocation
    - destroys structure
    - + cheap
  - 3 Galerkin projection + gappy POD approximation of residual
    - destroys structure
    - + cheap
  - 4 proposed method
    - + preserves structure
    - + cheap
- reduced-order-model parameters
- $\Phi \in \mathbb{R}^{N \times m}$ : POD,  $m = 18$  chosen via 99% ‘energy criterion’
  - sample indices  $n_Z = 30$
  - $\Phi_f \in \mathbb{R}^{N \times m_f}$ : POD,  $m_f = m = 10$
  - train at 3 configurations, test at a new configuration



	Galerkin	Galerkin + collocation	Galerkin + LS recon.	proposed method
error	6.85%	18.7%	690%	7.0%
speedup	0.41	1.77	2.06	1.82

# Conclusions




- directly approximate reduced Lagrangian ingredients
  - + Lagrangian-structure preservation
  - + computational efficiency
- only reduced-order model delivering accuracy and speedup!
- future work
  - deploy on more realistic (larger, more highly nonlinear) problem
  - apply framework to preserve structure for other systems

# Acknowledgments

- Julien Cortial: useful discussions and the nonlinear-truss code
- This research was supported in part by an appointment to the Sandia National Laboratories Truman Fellowship in National Security Science and Engineering, sponsored by Sandia Corporation (a wholly owned subsidiary of Lockheed Martin Corporation) as Operator of Sandia National Laboratories under its U.S. Department of Energy Contract No. DE-AC04-94AL85000.
- We acknowledge support by the Department of Energy Office of Advanced Scientific Computing Research under contract 10-014804.



# Bibliography I

-  Astrid, P., Weiland, S., Willcox, K., and Backx, T. (2008).  
Missing point estimation in models described by proper  
orthogonal decomposition.  
*IEEE Transactions on Automatic Control*, 53(10):2237–2251.
-  Carlberg, K., Bou-Mosleh, C., and Farhat, C. (2011).  
Efficient non-linear model reduction via a least-squares  
Petrov–Galerkin projection and compressive tensor  
approximations.  
*International Journal for Numerical Methods in Engineering*,  
86(2):155–181.
-  Chaturantabut, S., Sorensen, D. C., and Steven, J. C. (2010).  
Nonlinear model reduction via discrete empirical interpolation.  
*SIAM Journal on Scientific Computing*, 32(5):2737–2764.

# Bibliography II



Grepl, M. A., Maday, Y., Nguyen, N. C., and Patera, A. T. (2007).

Efficient reduced-basis treatment of nonaffine and nonlinear partial differential equations.

*ESAIM-Mathematical Modelling and Numerical Analysis (M2AN)*, 41(3):575–605.



Hairer, E., Lubich, C., and Wanner, G. (2006).

*Geometric numerical integration: structure-preserving algorithms for ordinary differential equations*, volume 31. Springer Verlag.



Lall, S., Krysl, P., and Marsden, J. (2003).

Structure-preserving model reduction for mechanical systems.

*Physica D: Nonlinear Phenomena*, 184(1-4):304–318.

# Bibliography III



Marsden, J. and West, M. (2001).

Discrete mechanics and variational integrators.

*Acta Numerica*, 10(357):514.



Nguyen, N. C. and Peraire, J. (2008).

An efficient reduced-order modeling approach for non-linear parametrized partial differential equations.

*International Journal for Numerical Methods in Engineering*, 76:27–55.



Ryckelynck, D. (2005).

A priori hyperreduction method: an adaptive approach.

*Journal of Computational Physics*, 202(1):346–366.